

LSG LITHIUM COMPLEX 150 GREASE NO. 00, 0, 1, & 2

Heavy-Duty Lithium Complex Grease for Industrial Applications & Power Tools.

High-Performance Lubricant for Industrial Machinery and Power-Driven Components.

LSG LITHIUM COMPLEX 150 GREASE NO. 00, 0, 1, & 2



Is a high-performance, heavy-duty lubricant engineered for power tools and industrial machinery applications that demand exceptional mechanical stability and load-bearing capacity.

Designed to perform under tough operating conditions, it offers superior film strength and remarkable protection against wear, vibration, and moisture ingress.

Formulated with performance and equipment longevity in mind, making it an ideal solution for professional and industrial maintenance programs. It excels in environments where continuous operation and repeated mechanical stress are the norm, such as manufacturing plants, assembly lines, maintenance fleets, and job-site power equipment.

This grease designed to meet the rigorous standards of today's advanced machinery.

It features an advanced lithium complex thickener system, and a precisely engineered additive package.

This unique formulation technology ensures excellent adhesion to metal surfaces, reduces wear, and provides long-lasting protection.

Its composition delivers strong thermal stability, outstanding mechanical integrity, excellent resistance to water washout, and high-load applications—ensuring optimal lubrication performance in handheld tools, electric motors, and other compact power-driven components exposed to heat, vibration, and variable loads.

KEY FEATURES

- **Lithium complex thickener** for high-temperature stability in power tool gearboxes bearings and industrial applications providing long term protection and longer life.
- **Strong resistance to water washout**, protecting components from moisture ingress that can damage your equipment.
- **Excellent mechanical and shear stability**, maintaining consistency under high-speed operation and vibration.
- **Corrosion and oxidation protection**, extending the lifespan of internal tool components.
- **High film strength** and load-carrying ability, safeguarding gears and bearings from wear.
- **Available in NLGI No. 00, 0, 1 & 2 consistency** for versatile application methods and operating conditions, such as centralized systems and manual regreasing operations.

CUSTOMER BENEFITS

- ✓ Maintains performance under heavy mechanical stress and continuous tool reducing part wear and increasing tool life.
- ✓ Resists water intrusion and protects parts from wet environments, crucial for extending industrial equipment and job-site tools.
- ✓ Reduces equipment wear and extends tool bearing and gear life, lowering replacement costs.
- ✓ Withstands high operating temperatures and load pressures, ensuring reliable tool function.
- ✓ Offers long service intervals and excellent thermal resistance, contributing to reduced tool and equipment maintenance.

APPLICATIONS

LSG Lithium Complex 150 Grease No. 00, 0, 1, & 2 are designed for high-performance industrial applications including:

- Electric and pneumatic power tools: Drills, saws, grinders, impact wrenches, jackhammers.
- Small machinery gearboxes: Handheld power equipment, compact industrial units.
- High-load bearings and gears within power tools and light industrial machinery.
- General lubrication points in manufacturing plants and assembly lines.
- General machinery and construction equipment where a multi-purpose grease is needed.
- Centralized lubrication systems requiring softer consistencies (NLGI No. 00, 0 & 1).

PACKAGING:



Cartridges
14 oz.



Pails
35 lbs.



Kegs
120 lbs.



Drums
400 lbs.

*Custom and Bulk Packaging available upon request.

TYPICAL PROPERTIES

Property	No. 00	No. 0	No. 1	No. 2	Test Method
NLGI Grade	00	0	1	2	ASTM D217
Worked Penetration (60X)	400 – 430	355 – 385	310 – 340	265 – 295	ASTM D217
Dropping Point (°C)	-	-	>260	>260	ASTM D2265
Base Oil Viscosity @ 40°C (cSt)	150	150	150	150	ASTM D445
Four Ball Weld Load (kg)	400	400	400	400	ASTM D2596
Four Ball Wear (mm)	0.45	0.45	0.45	0.45	ASTM D2266
Timken OK Load (lbs)	45	45	45	45	ASTM D2509
Water Washout, % @ 79°C	-	-	<3	<3	ASTM D1264
Color	Red	Red	Red	Red	Visual
Texture	Smooth / Tacky	Smooth / Tacky	Smooth / Tacky	Smooth / Tacky	Visual



Typical properties reflect the expected results within normal production tolerances but do not constitute a specification. Minor variations that do not impact product performance may occur during standard manufacturing processes or at different blending locations. The information provided here is subject to change without notice.

Health and Safety:

When used as intended, this product is not expected to pose any health risks or safety concerns. To minimize exposure, avoid direct skin contact and wear resistant gloves when handling used lubricants. If contact occurs, wash the affected area immediately with soap and water. For comprehensive guidelines on safe handling and detailed product information, please refer to the Material Safety Data Sheet (MSDS) available on our website. <https://lonestargl.com>